

What is claimed is:

1. A snap lock device for hingedly securing an extension to a downspout, said device
5 comprising:

a first member;

said first member including:

a head;

a shank extending from said head, said shank extending through a first hole defined by
the extension and through a second hole defined by the downspout;

a second member cooperating with said first member; and

said second member defining an aperture for the locking reception therein of said shank for
locking the extension and downspout together.

2. A snap lock device for hingedly securing an extension to a downspout as set forth in
claim 1 further including:

a third member;

said third member including:

a further head;

a further shank extending from said further head, said further shank extending through a
third hole spaced from said first hole and defined by the extension and through a fourth
hole spaced from said second hole and defined by the downspout;

a fourth member cooperating with said third member;

said fourth member defining a further aperture for the locking reception therein of said further shank for locking the extension and downspout together so that folding of the extension against the downspout is permitted for facilitating yard maintenance.

5

3. A snap lock device for hingedly securing an extension to a downspout as set forth in claim 1 wherein

said head is of disc shaped configuration.

4. A snap lock device for hingedly securing an extension to a downspout as set forth in claim 1 wherein

said head is metallic.

5. A snap lock device for hingedly securing an extension to a downspout as set forth in

claim 1 wherein

said head is fabricated from Aluminum.

6. A snap lock device for hingedly securing an extension to a downspout as set forth in claim 1 wherein

said shank is of cylindrical configuration.

7. A snap lock device for hingedly securing an extension to a downspout as set forth in

1000110-112301
"OFF FOOT"

15

20

said cylindrical shank has a proximal and a distal end and a cylindrical surface, said shank extending normal to said head.

5 8. A snap lock device for hingedly securing an extension to a downspout as set forth in
claim 7 wherein

said shank has a diameter which is less than a further diameter of said head.

9. A snap lock device for hingedly securing an extension to a downspout as set forth in claim 8 wherein
 said cylindrical surface defines an annular ridge such that when said shank extends through said aperture of said second member, said annular ridge locks said second member relative to said first member.

15 10. A snap lock device for hingedly securing an extension to a downspout as set forth in
claim 1 wherein

said second member is of disc shaped configuration.

11. A snap lock device for hingedly securing an extension to a downspout as set forth in

20 claim 1 wherein

said second member is fabricated from a plastics material.

~~CONFIDENTIAL~~
55
A22

103 5735665
12. A snap lock device for hingedly securing an extension to a downspout as set forth in claim 1 wherein

said second member is fabricated from NYLON.

502 3911954
13. A snap lock device for hingedly securing an extension to a downspout as set forth in claim 8 wherein

said second member has a first diameter which is the same as said further diameter of said head.

536 3911954
14. A tool device for attachment to a jaw of a pair of pliers for assisting fastening of a snap lock device as set forth in claim 1, said tool device comprising:

a cylindrical member having a first and a second face and a longitudinal axis and a cylindrical outer surface, said cylindrical member defining a coaxial bore extending between said first and second face;

said first face defining a slot which extends diametrically across said first face for the reception therein of the jaw of the pair of pliers;

said cylindrical member defining a threaded bore which extends normal to said slot, said threaded bore extending from said cylindrical outer surface to said slot;

a fastener cooperating with said threaded bore such that said fastener removably fastens said cylindrical member to the jaw of the pair of pliers;

said second face of said cylindrical member defining a cavity which is disposed coaxially relative to said longitudinal axis, said cavity having substantially the same dimensions as said second member, the arrangement being such that when a second member is disposed within said cavity,

~~insertion of said shank within said aperture of said second member by the pliers is permitted.~~

15. A snap lock device for hingedly securing an extension to a downspout, said device comprising:

5 a first member;

said first member including:

a head;

a shank extending from said head, said shank extending through a first hole defined by

the extension and through a second hole defined by the downspout;

obv. nuts or washers for post pipe
a second member cooperating with said first member;

said second member defining an aperture for the locking reception therein of said shank for locking the extension and downspout together;

12
a third member;

said third member including:

15 a further head;

a further shank extending from said further head, said further shank extending through a

third hole spaced from said first hole and defined by the extension and through a fourth

hole spaced from said second hole and defined by the downspout;

obv. nuts or washers for post rod
a fourth member cooperating with said third member; and

20 said fourth member defining a further aperture for the locking reception therein of said further shank for locking the extension and downspout together so that folding of the extension against the downspout is permitted for facilitating yard maintenance.

1000110-112301

A

said first member including:

a shank extending from said head, said shank extending through a first hole defined by the extension and through a second hole defined by the downspout;

said second member defining an aperture for the locking reception therein of said shank for locking the extension and downspout together;

said third member including:

a further shank extending from said further head, said further shank extending through a third hole spaced from said first hole and defined by the extension and through a fourth hole spaced from said second hole and defined by the downspout;

said fourth member defining a further aperture for the locking reception therein of said further shank for locking the extension and downspout together so that folding of the extension against the downspout is permitted for facilitating yard maintenance;

said head being metallic;

said shank being of cylindrical configuration;

said cylindrical shank having a proximal and a distal end and a cylindrical surface, said shank extending normal to said head;

said shank having a diameter which is less than a further diameter of said head;

5 said cylindrical surface defining an annular ridge such that when said shank extends through said aperture of said second member, said annular ridge locks said second member relative to said first member;

said second member being of disc shaped configuration;

said second member being fabricated from a plastics material; and

said second member having a first diameter which is the same as said further diameter of said head.

10003310-112301
15